

Product Specifications



Changing the Way the World Communicates

Mini-PVx v.17 Specifications



Mini-ITX Slim Desktop / Slim Tower with mounting feet.

Processor – Memory and Disk

Intel® Atom™ Processor D510 (Dual Core, 1M Cache, 1.66 GHz)
1GB 128M x 64-Bit DDR2-800 CL 200-Pin SODIMM
1x160GB SATA hard drive

Dimensions

Height 70mm
Width 268mm
Depth 290mm
Gross Weight 3.2kg

Front Panel

Buttons	Power On/Off button	LEDs	Power LED
Connectors	Dual USB and Audio		

Operating Environment (System)

RoHS Compliant 6/6, Pb free	
Operating Temperature Range	0 - 55°C
Non-Operating Temperature Range	-40 - +70°C
Humidity Range	8% to 90% non-condensing
Non-Operating Humidity Range	5% to 95% non-condensing

Power Supply

120W High efficient Flex ATX PSU

Regulatory (Power Supply)

Power Supply Safety / EMC	USA - UL listed, FCC Canada - CUL listed	Europe/CE Mark Germany - TUV Certified N 60950/IEC 60950-
	Compliant	

Protocols Supported

VoIP – H323 Ver. 3
VoIP – SIP
VoIP – NOP (WTL Proprietary High Quality 14:1 Compression)

Operating System

Solaris 10

Voice Support & Capacity

Maximum number of simultaneous calls: 300

Maximum call set up: BHCC Rate (Busy Hour Call Completion) over 50,000 per PVx

Voice codecs: G723.1, G726, G728, G729